



PRODUCTION OF DETERGENTS - CARS - INDUSTRY - COMMUNITY - HEAVY GOODS VEHICLES

TEMPER -40

rev. **02**

date: 31/07/2023

antifreeze liquid for cooling circuits

CHARACTERISTICS:: Non-foaming injection-extraction cleaner for carpets and upholstery. Thanks to its suspending surfactants, it attracts dirt to the surface, allowing it to be easily removed. It also leaves a pleasant fragrance. Suitable for upholstery washers.



INSTRUCTIONS FOR USE:

- Pure resists up to 40°C
- Diluted 1:1 resists up to 20°C
- Diluted 1:2 resists up to 10°C

PARAMETERS	VALUES	ANALYSIS METHOD
Physical appearance	Liquid	
Smell	Characteristic	
Specific weight (kg/lt)	1.06-1.08 a 20 °C	(INT1)
Active matter (brix scale)	16-18°Bx a 20 °C	(INT2)
рН	9 (10g/lt at 23°C)	(INT3)
Flammability	None	
Hazard symbol	GHS07	
Surfactants	None	

This product is distributed in compliance with Legislative Decree 14.03.03 n° 65, Dir. 94/1/EEC, Dir. 67/548/EEC and subsequent amendments

SANITARY INFORMATION: In case of contact with skin and eyes, rinse thoroughly. with water. In case of ingestion, do not induce vomiting, keep the subject at rest and seek medical attention.



GO TO THE DEDICATED CATEGORY ON OUR WEBSITE WWW.EURODET.IT