



## NOCAL

rev. **02**

date: **29/08/2023**

### Dielectric anti-limescale additive

**CHARACTERISTICS:** preventive anti-limescale product. thanks to its chelating properties, it prevents water from depositing insoluble salts and lime scale in coils and steam boilers. suitable for pressure washers, irons, steamers.



**INSTRUCTIONS FOR USE:** put the product in the pressure washer tray, 1 drop every 10/20 seconds.

PARAMETERS	VALUES	ANALYSIS METHOD
Physical appearance	liquid	
Smell	Characteristic	
Specific weight (kg/lt)	1.0-1.02 at 20 °C	(INT1)
Active matter (brix scale)	6- 9 °Bx at 20 °C	(INT2)
PH	12	(INT3)
Flammability	None	
Hazard symbol	GHS05	
Biodegradability	Over 90%	
Surfactants	Non-ionic	

This product is distributed in compliance with Legislative Decree 14.03.03 n° 65, Dir. 94/1/EEC, Dir. 67/548/EEC and subsequent amendments

**SANITARY INFORMATION:** In case of contact with skin and eyes, rinse thoroughly. with water. In case of ingestion, do not induce vomiting, keep the subject at rest and seek medical attention.

**DILUIZIONI / DILUTION**  
**per 1 litro d'acqua / for 1 liter of water**  
**5/10g**

---



---



---



---



**GO TO THE DEDICATED CATEGORY ON OUR WEBSITE**  
**WWW.EURODET.IT**