



Eurodet

PRODUCTION OF DETERGENTS - CARS - INDUSTRY - COMMUNITY - HEAVY GOODS VEHICLES

OXFORT

rev.

02

date:

29/08/2023

Anti-limescale additive

CHARACTERISTICS: preventive anti-limescale product. thanks to its chelating properties, it prevents water from depositing insoluble salts and lime scale in coils and steam boilers. suitable for pressure washers, irons, steamers.



INSTRUCTIONS FOR USE: put the product in the pressure washer tray, 1 drop every 10/20 seconds.

PARAMETERS	VALUES	ANALYSIS METHOD
Physical appearance	liquid	
Smell	Characteristic	
Specific weight (kg/lt)	1.0-1.02 at 20 °C	(INT1)
Active matter (brix scale)	6- 9 °Bx at 20 °C	(INT2)
PH	12	(INT3)
Flammability	None	
Hazard symbol	GHS05	
Biodegradability	Over 90%	
Surfactants	Non-ionic	

This product is distributed in compliance with Legislative Decree 14.03.03 n° 65, Dir. 94/1/EEC, Dir. 67/548/EEC and subsequent amendments

SANITARY INFORMATION: In case of contact with skin and eyes, rinse thoroughly. with water. In case of ingestion, do not induce vomiting, keep the subject at rest and seek medical attention.

DILUIZIONI / DILUTION
 per 1 litro d'acqua / for 1 liter of water
 5/10g



GO TO THE DEDICATED CATEGORY ON OUR WEBSITE
WWW.EURODET.IT