



TEMPER G13

rev. **02**

date: **31/04/2024**

Antifreeze liquid for G13 cooling circuits

CHARACTERISTICS: Antifreeze liquid for radiators useful in all seasons. It respects the environment as it is free of amines and nitrites. It contains anti-foaming and anti-redeposition additives and keeps the cooling circuit clean. It is anti-freezing and anti-evaporating, ideal for any type of cooling. with a 100% Silanized Organic Acid technology inhibitor package.

PASSEND FOR G 013/TL 774 J.

al 22% resiste sino a -10°C

al 30% resiste sino a -15°C

al 35% resiste sino a -20°C

al 40% resiste sino a -25°C

al 45% resiste sino a -30°C

al 50% resiste sino a -36°C



PARAMETERS	VALUES	ANALYSIS METHOD
Physical appearance	Viscous liquid	
Smell	Characteristic	
Specific weight (kg/lit)	1.11-1.13 a 20 °C	(INT1)
Active matter (brix scale)	30-32°Bx a 20 °C	(INT2)
pH	9 (10g/lit at 23°C)	(INT3)
Flammability	None	
Hazard symbol	GHS07, GHS08	
Surfactants	None	

This product is distributed in compliance with Legislative Decree 14.03.03 n° 65, Dir. 94/1/EEC, Dir. 67/548/EEC and subsequent amendments

INFORMAZIONI IGIENICO-SANITARIE: : In caso di contatto con la pelle e gli occhi, lavare abb. con acqua. In caso di ingestione non provocare vomito, tenere il soggetto a riposo e richiedere l'intervento di un medico.



GO TO THE DEDICATED CATEGORY ON OUR WEBSITE
WWW.EURODET.IT



Eurodet

PRODUZIONE DETERGENTI - AUTO - INDUSTRIA - COMUNITÀ - MEZZI PESANTI

TEMPER G13

rev.

02

data:

31/04/2024

Antifreeze liquid for G13 cooling circuits

TEMPER G13 EXCEEDS THE REQUIREMENTS OF THE FOLLOWING STANDARDS NATIONAL OR INTERNATIONAL:

BS 6580(GB)
SAE J 1034
CUNA NC 956-16(I)
FVV Heft R 443(D)
JIS K 2234(J)
UNE 26361-88(E)
Afnor R 15/601(F)
KSM 2142 (K)
EMPA (CH)
ASTM D 3306/4985/6210 Type 1-FF
NATO S 759
E/L 1415c (MIL Italy)



TEMPER G13 MEETS THE FOLLOWING MANUFACTURERS' REQUIREMENTS:

Audi: TL 774 J
Bentley: TL 774 J
Bugatti: TL 774 J
Lamborghini: TL 774 J
Seat: TL 774 J
Skoda: TL 774 J
VW: TL 774 J



VAI ALLA CATEGORIA DEDICATA NEL NOSTRO SITO
WWW.EURODET.IT

DATA SHEET